

CERTIFICATE OF ACCREDITATION

The ANSI National Accreditation Board

Hereby attests that

MicroscOptics, Inc. 9126 Pineview Lake Court Linden, MI 48451

Fulfills the requirements of

ISO/IEC 17025:2017

and national standard

ANSI/NCSL Z540-1-1994 (R2002)

In the field of

CALIBRATION

This certificate is valid only when accompanied by a current scope of accreditation document. The current scope of accreditation can be verified at <u>www.anab.org</u>.





Jason Stine, Vice President Expiry Date: 10 April 2026 Certificate Number: AC-1218

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communiqué dated April 2017).



SCOPE OF ACCREDITATION TO ISO/IEC 17025:2017

AND

ANSI/NCSL Z540-1-1994 (R2002)

MicroscOptics, Inc.

9126 Pineview Lake Court Linden, MI 48451 James L. Short 248-328-0433

CALIBRATION

Valid to: April 10, 2026

Certificate Number: AC-1218

Length – Dimensional Metrology

| Parameter/Equipment | Range | Expanded Uncertainty of Measurement (+/-) | Reference Standard, Method, and/or Equipment |
|---|--|--|--|
| Microscopes ¹ Length & Linearity (Eyepiece micrometers and image systems) | (0.000 4 to 1) in (0.01 to 25) mm | 14 μin 0.34 μm | Stage Micrometer |
| Linear Stage Measurement Devices ¹ Length & Linearity, X, Y axis's Length & Linearity, Z-axis (Optical & Digital Comparators, MeasureScopes, and CNC Video Microscopes) | (1 to 12) in (0.01 to 300) mm (0.02 to 105) mm | 175 μin 1.1 μm 0.32 μm | Glass Scales, Step Gage, Gage Blocks |
| Optical and Contact Profilometers ¹ Ra Step Height Angle Capable Measurement Devices ^{1,2} | Up to 3 μm (0.02 to 105) mm | 40 nm 0.13 μm | Surface Finish Specimen Step Gage, Gage Blocks |
| (Optical & Digital Comparators and Image Systems) | (0 to 360)° | 2' | Angle Blocks |



www.anab.org



Length – Dimensional Metrology

| Parameter/Equipment | Range | Expanded Uncertainty of Measurement (+/-) | Reference Standard, Method, and/or Equipment |
|--|--------------|--|--|
| Magnification ¹ (Optical & Digital Comparators, Eye Loupes, and Image Systems) | Up to 2 000X | 0.13 % of the nominal magnification | Glass Scale Comparison |

Calibration and Measurement Capability (CMC) is expressed in terms of the measurement parameter, measurement range, expanded uncertainty of measurement and reference standard, method, and/or equipment. The expanded uncertainty of measurement is expressed as the standard uncertainty of the measurement multiplied by a coverage factor of 2 (k=2), corresponding to a confidence level of approximately 95%. Notes:

1. On-site calibration service is available for this parameter, since on-site conditions are typically more variable than those in the laboratory, larger measurement uncertainties are expected on-site than what is reported on the accredited scope, ' = arc-minute.

- 2.
- 3. This scope is formatted as part of a single document including Certificate of Accreditation No. AC-1218.

Jason Stine, Vice President



Version 018 Issued: March 29, 2024

www.anab.org